

Voltage Code Designations

Voltage	Code
120/240 Split Phase	1
120V Single Phase	11
240V Single Phase	12
120/208V Three Phase, WYE	2
120/240V Three Phase, High-Leg, DELTA	3
120V Three Phase, DELTA	31
277/480V Three Phase, WYE	4
480V Three Phase, DELTA	5
480V Three Phase, Corner Grounded, DELTA	51
240V Three Phase, DELTA	6
240V Three Phase, Corner Grounded, DELTA	61
220/380V Three Phase, WYE	7
347/600V Three Phase, WYE	8
600V Three Phase, DELTA	9
600V Three Phase, Corner Grounded, DELTA	91

Not ALL APT models are available in ALL voltages; check the current cutsheet for the product to confirm available voltages.

Option Code Designations	
Option Description	Code
Surge Counter, six-digit LCD counter	X
Remote Locatable Display on 4ft Cable (custom cable lengths available)	E
Noise Filtering-Extended Range & Attenuation (400kA & 500kA models only)	F
Rotary Disconnect Switch, Bussmann, UL 98	D
Thru-Door Rotary Disconnect Switch, Bussmann, UL98, E1 Enclosure only	T
NEMA 1/12/3R/4	E1
NEMA 4X Non-Metallic	4X
NEMA 4X Stainless Steel	4S
NEMA 1 Flush Mount	FM
NEMA 1 pullbox 'indoor' includes 'E' option	P1
Remote Monitor (order separately)	RM
Audible Alarm & Dry Contacts (XD & XC)	A
Flush Mount Kit (XD & XC)	Consult Factory
Delete Option Available on all models	Consult Factory